



1750Mbps Dual Band PCI-E Wireless Adapter

CF-WP1750

Hardware Specification	RTL8814AE
Support Protocol Standards	IEEE802.11ac, IEEE802.11n, IEEE802.11b, IEEE802.11g, IEEE802.11a
Antenna	External 4*3dBi dual band detachable omnidirectional antenna
Physical Interface	PCI EXPRESS X1
Wireless Rate	2.412-2.472GHz : 450Mbps 5.180-5.825GHz : 1300Mbps
Receive Sensitivity	5G 11ac
	VHT80M MCS9:-55dBm @10% PER
	HT40M MCS7: -65dBm @10% PER
	HT20M MCS7: -68dBm @10% PER
	2.4G 11n
	HT40M MCS7: -65dBm @10% PER
	HT20M MCS7: -68dBm @10% PER
	OFDM 54M:-70dBm@10% PER
	11b 11M:-81dBm@8% PER
Transmit Power	20dbm
LED Indicator	Link/Act
Support System	Microsoft Windows 7 32/64 , Windows 10 32/64
Product Size	247*121*21mm
Working Environment	Working Temperature: 0℃~40℃
	Storage Temperature: -40℃~70℃
	Working Humidity: 10%~90%RH Non-condensing
	Storage Humidity: 5%~90%RH Non-condensing