

COMFAST®



WiFi
Transfer Tool



Security
Monitoring Partner



Outdoor
WiFi Cover



WiFi Base
Station



CF-E315D

Hardware Specification	MTK7628KN RAM: DDR 8MB; Flash: 4MB;
Antenna	2*12dBi Internal Dual Polarization Antennas
Wireless Standard	IEEE802.11b/g/n
RF Parameters	Output Power: 82mW(19dBm); Receiving Sensitivity: -96dBm; WorkingFrequency:2.412~2.472GHz
Modulation Mode	DSSS : DBPSK@1Mbps、 DQPSK@2Mbps、 CCK@5.5/11Mbps OFDM : BPSK@6/9Mbps、 QPSK@12/18Mbps、 16-QAM@24Mbps 64-QAM@48/54Mbps MIMO-OFDM : MCS 0-15
Transmission Rate	2.4GHz: 300Mbps
Physical Ports	1* 10/100Mbps WAN RJ45 Ethernet Port; 1* 10/100Mbps LAN RJ45 Ethernet Port; 1* Master-slave mode DIP switch, 1*DC Port; 1* RESET Button
Indicator	8* Indicators:Power/WAN/LAN/WiFi/Signal Strength
Display	Rear digital display
Power	9V~24V POE power adapter; support DC power supply
Power Consumption(Max)	<5W
IP Index	2KV Lightning Protection; IP65
MTBF	>250000H
Installation Way	Wall-mounted/Pole-mounted
Case	Plastic Case (Imported ABS Material)
Physical Features	Size: 262*80*53mm; Weight: 0.32KG Working Temperature:- 10℃~55℃;
Working Environment	Storage Temperature: -50℃~75℃; Working Humidity: 10%~90%RH Non-condensing; Storage Humidity: 5%~90%RH Non-condensing