

COMFAST®

1200Mbps
Outdoor Wireless AP



Quality
Chipset



POE Power
Supply



Lightning-proof



Rain-proof



CF-EW72 V2

Hardware Specification	MT7621DAT+MT7613BEN+MT7603E; DDR: 128MB; Flash: 16MB;Built in Watchdog Chipset; PA Chipset: 2.4G KCT8227D; Supports the maximum number of end users:120+
Antenna	External 2*5dBi Antennas
Wireless Rate	2.4GHz :300Mbps 5GHz : 867Mbps
RF Parameters	Output Power (Max): 200mW （23dBm） ; Receiving Sensitivity (Min): -96dBm; Frequency: 802.11b/g/n : 2.412GHz-2.484GHz 802.11ac/n/a : 5.180GHz-5.825GHz
Modulation Mode	11b: DSS:CCK@5.5/11Mbps,DQPSK@2Mbps,DBPSK@1Mbps 11a/g: OFDM:64QAM@48/54Mbps,16QAM@24Mbps,QPSK@12/18Mbps, BPSK@6/9Mbps 11n:MIMO-OFDM:BPSK,QPSK,16QAM,64QAM 11ac:MIMO-OFDM:BPSK,QPSK,16QAM,64QAM,256QAM
Physical Ports	1*10/100/1000Mbps LAN RJ45 Ethernet Port; 1*10/100/1000Mbps WAN RJ45 Ethernet Port; 1*Reset Buttons
Indicator	WAN, LAN, WiFi,Power
Power	Power Supply: 802.3af/at POE Power Supply(0-100m); Power Adapter: 48V 0.32A POE Power Adapter(Configured)
Power Consumption(Max)	<13W
IP Index	Ip66
MTBF	>250000H
Installation Way	Wall-mounted/Pole-mounted
Case	Plastic Case (Imported ABS Material)
Physical Features	Size: 353*85*43.5mm
Working Environment	Working Temperature:-40℃~55℃; Storage Temperature: -40℃~70℃; Working Humidity: 10%~90%RH Non-condensing; Storage Humidity: 5%~95%RH Non-condensing