

COMFAST®

1200Mbps Outdoor Wireless AP



MediaTek
Chipset



POE Power
Supply



Lightning-proof



Rain-proof



CF-EW74 V2

Hardware Specification	MT7628DAN+MT7613BEN DDR: 64MB; Flash: 8MB; PA Chipset: 2.4G SKY85330, 5.8G SKY85735; Supports the maximum number of end users:64
Antenna	External 2*5dBi Antennas
Wireless Rate	2.4GHz :300Mbps 5GHz : 867Mbps
RF Parameters	Output Power (Max): 500mW (27dBm); Receiving Sensitivity (Min): -96dBm; Frequency: 802.11b/g/n : 2.412GHz-2.484GHz 802.11ac/n/a : 5.180GHz-5.825GHz
Modulation Mode	11b: DSS:CCK@5.5/11Mbps,DQPSK@2Mbps,DBPSK@1Mbps; OFDM:64QAM@48/54Mbps,16QAM@24Mbps,QPSK@12/18Mbps, BPSK@6/9Mbps 11n:MIMO-OFDM:BPSK,QPSK,16QAM,64QAM 11ac:MIMO-OFDM:BPSK,QPSK,16QAM,64QAM,256QAM
Physical Ports	1*10/100Mbps WAN(LAN) RJ45 Ethernet Port; 1*Reset Buttons
Indicator	Network port, WiFi,Power 3*signal strength indicators
Power	Power Supply: 24V POE Power Supply(0-100m); Power Adapter: 24V 0.5A POE Power Adapter(Configured)
Power Consumption(Max)	<12W
IP Index	Ip66
MTBF	>250000H
Installation Way	Wall-mounted/Pole-mounted
Case	Plastic Case (Imported ABS Material)
Physical Features	Size: 380*54mm
Working Environment	Working Temperature: -10 ~55 ; Storage Temperature: -40 °C~70 °C; Working Humidity: 10%~90%RH Non-condensing; Storage Humidity: 5%~90%RH Non-condensing