



1300Mbps 11AC Dual Frequency Wireless Ceiling AP




Qualcomm
Chipset



Watchdog



WiFi
Coverage



OpenWRT OS



CF-E375AC V2

Application



Restaurant



Guesthouse



Beauty Salons

Hardware Specifications	Chipset: Qualcomm QCA9563+QCA8337+QCA9886; DDR: 128MB; Flash: 16MB; PA: 2.4G SKY85330-11, 5.8G SKY85735-11; Built in Watchdog Chipset
Antenna	Built in 5*3dBi Antennas
Transmission Rate	2.4GHz: 450Mbps; 5.8GHz: 867Mbps
RF Parameters	Output Power (Max): 200mW (23dBm) ; Receiving Sensitivity (Max): -96dBm; Frequency: 5.8GHz: 5.18-5.825GHz; 2.4GHz : 2.412GHz-2.472GHz
Physical Ports	1* 10/100/1000Mbps WAN RJ45Ethernet Port; Support POE Power Supply; 1* 10/100M/1000Mbps LAN Ethernet Port; Support POE Power Supply; 1* RESET Button
Indicator	Three Color Indicator
Power	Power Supply: 802.3af/802.3at POE Power Supply(0-100m); Power adapter: 48V 0.32A POE Power Adapter(Configured)
Power Consumption(Max)	<13W
IP Index	IP31
MTBF	>250000H
Installation Way	Ceiling-mounted, Wall-mounted
Case	Plastic Case(Imported ABS Material)
Physical Features	Size: 220*220*35mm
Working Environment	Working Temperature: 0℃~40℃; Storage Temperature: -40℃~70℃; Operation Humidity: 10%~90%RH Non condensing; Storage Humidity: 5%~95%RH Non condensing