

COMFAST®

300Mbps WiFi Extender
In Wall Access Point



WiFi




Network



Tel



Application



Hotel



Dormitory



Office

CF-E533N-R-W

Hardware Specifications	Chisept: MT7628KN; DDR: 8MB; Flash: 2MB
Antenna	2*2dBi Internal Antennas
Wireless Standards	IEEE802.11b/g/n
RF Parameter	Output Power(Max): 80mW(19dBm); Receiving Sensitivity(Max): -91dBm; Working Frequency: 2.412GHz-2.4835GHz
Modulation Mode	DSSS : DBPSK@1Mbps, DQPSK@2Mbps, CCK@5.5/11Mbps; OFDM : BPSK@6/9Mbps, QPSK@12/18Mbps, 16-QAM@24Mbps, 64-QAM@48/54Mbps; MIMO-OFDM: MCS 0-15
Wireless Rate	300Mbps
Physical Ports	1* 10/100Mbps WAN RJ45 Port; Support 48V POE; 1* 10/100Mbps LAN RJ45 Port; 2* RJ11 Port;
Indicator	WiFi Indicator, LED Light
Power	Power Supply: 802.3af/802.3at POE Power Supply(0-100m); (If you do not have a POE power supply, you need to purchase a POE power module or use it with a POE power supply.)
Power Consumption	<5W
IP Index	IP41
MTBF	>250000H
Installation Way	In Wall Installation
Case	Plastic Case (Imported ABS Material)
Physical Features	Size: 86*86*33mm; Weight: 101g
Working Environment	Working Temperature: 0 C°~40C;° Storage Temperature: -40°C~70°C; Operation Humidity: 10%~90%RH Non-condensing; Storage Humidity: 5%~90%RH Non-condensing